



UPGRADE YOUR SAFETY WITH US

+91 97243 42142

info.aurexfire@gmail.com

www.aureliusgroups.com

CLEAN AGENT STORED PRESSURE 4KG FIRE EXTINGUISHER **MS BODY** PRODUCT DATA SHEET

1. PRODUCT OVERVIEW

1	Brand Name	AUREX
2	Model Number	AICA-4001
3	Extinguisher Type	Clean Agent (Portable)
4	Capacity	4 KG
5	Fire Classification	Class A / B / C
6	Fire Rating	2A 34B
7	Coverage Area	3.5 Meters for 14 sec. Minimum
8	Compliance Standard	IS 15683:2024

2. STANDARD MATERIAL OF CONSTRUCTION

1	Cylinder thickness	1.4 MM mild steel
2	valve	Brass / Aluminium
3	valve Type	CE (NRV) / Normal
4	Nozzle & Discharge fitting	M.S. Nozzle & M.S. Fitting
5	O-Ring	Rubber
6	Plunger	Brass
7	Spring	Steel
8	Pressure Guage	Brass
9	Syphon Tube	Plastic
10	Charge	FK-5-1-12 / FM-200 / HFC 236fa
11	Handle & Lever	Mild Steel
12	External Coating	Epoxy Powder Coating
13	Corrosion resistance	Anti-Corrosive Coating
14	Wall bracket	MS Powder Coated

3. TECHNICAL SPECIFICATION

1	Minimum Discharge Time	14 SEC.
2	Effective Discharge Reach	3.5 METER
3	Hydraulic Pressure Test	35 BAR
4	Bursting Pressure Test	60 BAR
5	Working Pressure	15 BAR
6	Operating Temprature Range	-30°C to +60°C
7	Type Test Standard	IS 15683 : 2024

AURELIUS INDUSTRIES LLP

At-savdi, Butiyu, Survey no: 49/1p1, Tankara-latipar road, Morbi, Gujarat, 363650

4. PACKAGING & STORAGE

PARTICULAR	DETAILS
Storage Condition	Cool & Dry Place
Service Frequency	As Per IS 2190
Annual Maintenance	Recommended
Refilling Interval	Every 5 Years
Product Life	Approx. 10 Years

5. OPERATING METHOD

PASS METHOD

P – Pull the Pin
A – Aim at Base of Fire
S – Squeeze the Handle
S – Sweep Side to Side

6. FEATURES

- High Fire Suppression Efficiency
- Easy Operation & Maintenance
- Corrosion Resistant Body
- Fast Discharge Action
- Refillable & Rechargeable
- Long service life