



UPGRADE YOUR SAFETY WITH US

+91 97243 42142

info.aurexfire@gmail.com

www.aureliusgroups.com

ABC STORED PRESSURE 4KG (50% MAP) FIRE EXTINGUISHER **SS BODY** PRODUCT DATA SHEET

1. PRODUCT OVERVIEW

1	Brand Name	AUREX
2	Model Number	AID-4501-SS
3	Extinguisher Type	ABC Stored Pressure
4	Capacity	4 KG
5	Fire Classification	Class A / B / C
6	Fire Rating	3A 55B
7	Coverage Area	6 Meters for 14 sec. Minimum
8	Compliance Standard	IS 15683:2018

2. STANDARD MATERIAL OF CONSTRUCTION

1	Cylinder thickness	1.2 MM Stainless steel
2	valve	Brass / Aluminium
3	valve Type	CE (NRV) / Normal
4	Nozzle & Discharge fitting	M.S. Nozzle & M.S. Fitting
5	Hose	Braided PVC / EPDM
6	O-Ring	Rubber
7	Plunger	Brass
8	Spring	Steel
9	Pressure Guage	Brass
10	Syphon Tube	Plastic
11	Charge	50% MAP Dry Chemical Powder
12	Handle & Lever	Mild Steel
13	External Coating	Epoxy Powder Coating
14	Corrosion resistance	Anti-Corrosive Coating
15	Wall bracket	MS Powder Coated

3. TECHNICAL SPECIFICATION

1	Minimum Discharge Time	14 SEC.
2	Effective Discharge Reach	6 Meter
3	Hydraulic Pressure Test	35 BAR
4	Bursting Pressure Test	70 BAR
5	Working Pressure	15 BAR
6	Operating Temperature Range	-30°C to +60°C
7	Type Test Standard	IS 15683 : 2018

AURELIUS INDUSTRIES LLP

At-savdi, Butiyu, Survey no: 49/1p1, Tankara-latipar road, Morbi, Gujarat, 363650

4. PACKAGING & STORAGE

PARTICULAR	DETAILS
Packaging Type	Corrugated Paper Box
Storage Condition	Cool & Dry Place
Service Frequency	As Per IS 2190
Annual Maintenance	Recommended
Refilling Interval	Every 5 Years
Product Life	Approx. 10 Years

5. OPERATING METHOD

PASS METHOD

- P** – Pull the Pin
- A** – Aim at Base of Fire
- S** – Squeeze the Handle
- S** – Sweep Side to Side

6. FEATURES

- High Fire Suppression Efficiency
- Easy Operation & Maintenance
- Corrosion Resistant Body
- Fast Discharge Action
- Refillable & Rechargeable
- Long service life