



UPGRADE YOUR SAFETY WITH US

+91 97243 42142

info.aurexfire@gmail.com

www.aureliusgroups.com

## FOAM STORED PRESSURE 9 LTR FIRE EXTINGUISHER **SS BODY**

### PRODUCT DATA SHEET

#### 1. PRODUCT OVERVIEW

|   |                     |                              |
|---|---------------------|------------------------------|
| 1 | Brand Name          | AUREX                        |
| 2 | Model Number        | AIF-9061-SS                  |
| 3 | Extinguisher Type   | Foam Stored Pressure         |
| 4 | Capacity            | 9 LTR                        |
| 5 | Fire Classification | Class A / B                  |
| 6 | Fire Rating         | 4A 233                       |
| 7 | Coverage Area       | 6 Meters for 35 sec. Minimum |
| 8 | Compliance Standard | IS 15683:2018                |

#### 2. STANDARD MATERIAL OF CONSTRUCTION

|    |                            |                            |
|----|----------------------------|----------------------------|
| 1  | Cylinder thickness         | 1.2 MM Stainless steel     |
| 2  | valve                      | Brass / Aluminium          |
| 3  | valve Type                 | CE (NRV) / Normal          |
| 4  | Nozzle & Discharge fitting | M.S. Nozzle & M.S. Fitting |
| 5  | Hose                       | Braided PVC                |
| 6  | O-Ring                     | Rubber                     |
| 7  | Plunger                    | Brass                      |
| 8  | Spring                     | Steel                      |
| 9  | Pressure Guage             | Brass                      |
| 10 | Syphon Tube                | Plastic                    |
| 11 | Content                    | AFFF 6%                    |
| 12 | Handle & Lever             | Mild Steel                 |
| 13 | External Coating           | Epoxy Powder Coating       |
| 14 | Corrosion resistance       | Anti-Corrosive Coating     |
| 15 | Wall bracket               | MS Powder Coated           |

#### 3. TECHNICAL SPECIFICATION

|   |                            |                 |
|---|----------------------------|-----------------|
| 1 | Minimum Discharge Time     | 35 SEC.         |
| 2 | Effective Discharge Reach  | 6 Meter         |
| 3 | Hydraulic Pressure Test    | 35 BAR          |
| 4 | Bursting Pressure Test     | 70 BAR          |
| 5 | Working Pressure           | 15 BAR          |
| 6 | Operating Temprature Range | -30°C to +60°C  |
| 7 | Type Test Standard         | IS 15683 : 2018 |

AURELIUS INDUSTRIES LLP

At-savdi, Butiyu, Survey no: 49/1p1, Tankara-latipar road, Morbi, Gujarat, 363650

## 4. PACKAGING & STORAGE

| PARTICULAR         | DETAILS              |
|--------------------|----------------------|
| Packaging Type     | Corrugated Paper Box |
| Storage Condition  | Cool & Dry Place     |
| Service Frequency  | As Per IS 2190       |
| Annual Maintenance | Recommended          |
| Refilling Interval | Every 3 Years        |
| Product Life       | Approx. 10 Years     |

## 5. OPERATING METHOD

### PASS METHOD

- P** – Pull the Pin
- A** – Aim at Base of Fire
- S** – Squeeze the Handle
- S** – Sweep Side to Side

## 6. FEATURES

- High Fire Suppression Efficiency
- Easy Operation & Maintenance
- Corrosion Resistant Body
- Fast Discharge Action
- Refillable & Rechargeable
- Long service life